


SUPRA®**Call Centre & Office**

H E A D S E T F O R

P H O N E S

- Lightweight, headband style headsets
- Fully adjustable headset and microphone
- Choice of voice tube or noise cancelling models. Noise cancelling version eliminates up to 75% of background noise
- Ideal for use in call centres, helpdesks - designed for all day comfort

**Voice Tube Diagram & Noise Cancelling Diagram**

- | | |
|---------------------|--|
| 1 Monaural Headband | 6 Voice Tube |
| 2 Binaural Headband | 7 Clothing Clip |
| 3 Single Receiver | 8 Quick Disconnect™ |
| 4 Dual Receivers | 9 Optional Noise Cancelling microphone |
| 5 Ear Cushion(s) | |

Product Specifications**Transmit Characteristics (typical)**

Sensitivity @ 1kHz	-39 ± 3.5dBV/Pa
Frequency Range	200 to 4000Hz
DC Range	1.5 to 5V
Output Impedance	< 250Ω
Noise Cancellation	10dB (Noise cancelling models only)
Typical Test Conditions	1.8VDC, 3.3KΩ DC Resis, 3.3KΩ AC Load

Receive Characteristics

Sensitivity @ 1kHz	23.5 ± 3dBPa/V (Monaural) 18 ± 3dBPa/V (Binaural)
Frequency Range	200 to 4000Hz
Acoustic Limit	24dBPa
Input Impedance	150 ± 50Ω (Monaural) 300 ± 50Ω (Binaural)
Typical Test Conditions	100mV Drive, 150Ω Source Impedance



Plantronics Ltd
Wootton Bassett, UK
T:+44 1793 842200
F:+44 1793 848853

Plantronics France
Colombes, France
T:+33.1.46.49.83.00
F:+33.1.46.49.83.09

Plantronics SrL
Milano, Italy
T:+39.0295.11900-1-2
F:+39.02.951.1903

Plantronics Spain
Madrid, Spain
T:+34 91 640.47.44
F:+34 91 640.47.46

Plantronics Denmark
Søborg, Denmark
T:+45 39551051
F:+45 39551052

Plantronics GmbH
Hürth, Germany
T:+49.22.33.399.0
F:+46.22.33.373274

Plantronics Nordic Region
Örebro, Sweden
T:+46 19 121930
F:+46 19 121933

Plantronics B.V
Hoofddorp, Netherlands
T:+31 23 5648025
F:+31 23 5628015

For more information, call us on
0800 410014
Alternatively, visit our website
www.plantronics.com

PLANTRONICS®
World Leader in Communications Headsets